HYDRAULIC MAGNET WITH TOP PLATE

HMTP 125





- MADE IN ITALY
- HANDLE & COLLECT METAL PLATES, BARS AND SCRAPS
- > IDEAL IN CONSTRUCTION SITES, **RECYCLING PLANTS & SCRAP YARDS**
- NO ELECTRIC CABLES & ON BOARD CONTROL UNIT NEEDED
- CONNECT IT TO THE SAME HYDRAULIC LINE, USED FOR **HYDRAULIC BREAKERS & CRUSHERS**
- LOWER PLATE IN SPECIAL WEAR-RESISTANT STEEL
- > ATTACHED TO THE EXCAVATOR BY TOP BRACKET & QUICK HITCHES
- THE TOP PLATE ALLOWS EASIER & MORE PRECISE MOVEMENTS

MATCH IT WITH



DATA SHEET	EU	USA
Carrier weight (minimum)	26 t	26 t
Carrier weight (recommended)	32 t	32 t
Magnet weight	1750 kg	3858 lb
Magnet diameter	1250 mm	49 inch
Engine power	7 kW	7 kW
Voltage	220 V	220 V
Required oil flow	100 - 200 L/min	26 - 52 gal/min
Oil pressure	180 bar	2611 psi
Scrap weight	900 kg	1984 lb
Plate weight	12000 kg	26455 lb