

HYDRAULIC MAGNET WITH TOP PLATE & TEETH HMT 150



- MADE IN ITALY
- HANDLE & COLLECT METAL PLATES, BARS AND SCRAPS
- IDEAL IN CONSTRUCTION SITES, RECYCLING PLANTS & SCRAP YARDS
- NO ELECTRIC CABLES & ON BOARD CONTROL UNIT NEEDED
- CONNECT IT TO THE SAME HYDRAULIC LINE, USED FOR HYDRAULIC BREAKERS & CRUSHERS
- LOWER PLATE IN SPECIAL WEAR-RESISTANT STEEL
- ATTACHED TO THE EXCAVATOR BY TOP BRACKET & QUICK HITCHES
- THE TOP PLATE ALLOWS EASIER & MORE PRECISE MOVEMENTS
- TEETH ALLOW TO EASILY COLLECT SMALL STEEL RODS, SHEETS & METAL SCRAPS IN THE GROUND

MATCH IT WITH



DATA SHEET

	EU	USA
Carrier weight (minimum)	34 t	34 t
Carrier weight (recommended)	40 t	40 t
Magnet weight	2850 kg	6283 lb
Magnet diameter	1500 mm	59 inch
Engine power	12 kW	12 kW
Voltage	220 V	220 V
Required oil flow	100 - 200 L/min	26 - 52 gal/min
Oil pressure	180 bar	2611 psi
Scrap weight	1200 kg	2646 lb
Plate weight	20000 kg	44092 lb