

HYDRAULIC MAGNET WITH TOP PLATE & TEETH

HMT 85



IT



- MADE IN ITALY
- HANDLE & COLLECT METAL PLATES, BARS AND SCRAPS
- IDEAL IN CONSTRUCTION SITES, RECYCLING PLANTS & SCRAP YARDS
- NO ELECTRIC CABLES & ON BOARD CONTROL UNIT NEEDED
- CONNECT IT TO THE SAME HYDRAULIC LINE, USED FOR HYDRAULIC BREAKERS & CRUSHERS
- LOWER PLATE IN SPECIAL WEAR-RESISTANT STEEL
- ATTACHED TO THE EXCAVATOR BY TOP BRACKET & QUICK HITCHES
- THE TOP PLATE ALLOWS EASIER & MORE PRECISE MOVEMENTS
- TEETH ALLOW TO EASILY COLLECT SMALL STEEL RODS, SHEETS & METAL SCRAPS IN THE GROUND

MATCH IT WITH



DATA SHEET

	EU	USA
Carrier weight (minimum)	10 t	10 t
Carrier weight (recommended)	14 t	14 t
Magnet weight	950 kg	2094 lb
Magnet diameter	850 mm	33 inch
Engine power	3,5 kW	3,5 kW
Voltage	220 V	220 V
Required oil flow	38 - 200 L/min	8 - 52 gal/min
Oil pressure	180 bar	2611 psi
Scrap weight	250 kg	551 lb
Plate weight	3500 kg	7716 lb

www.ramtec.it | info@ramtec.it |  +39 3499813724 | +39 0803388199



Data and pictures are not binding. The manufacturer can improve attachments without notice.